

## Product Features



**Positive tolerance**  
Guaranteed tolerance +3%  
Reliable power output



**High module efficiency**  
Module efficiency up to 15.5%  
Cells efficiency up to 18.5%



**Strong compressive strength**  
Certified to withstand high wind of 2400Pa  
and snow loads of 5400Pa




**High manufacture standards**  
certified to high standards by the  
most reputable labs  
According to IEC:61215: IEC:61730-1/2



**International Management System**  
Manufactured and certified according  
to ISO9001, ISO14001  
Quality and environment management system

## Leading Warranty in PV Industry

- 25 year transferrable power output warranty: 10 years / 90%, 25 years / 80%\*
- Linear performance warranty from SIMAX Power
- 12 year material and workmanship warranty



\* Please refer to Simax Solar Product Warranty for details.




**Photon**

## Electrical Characteristics

Parameters	SM660-240	SM660-245	SM660-250	SM660-255	SM660-260
Peak power [Wp] $P_{mpp}$	240W	245W	250W	255W	260W
Power Tolerance	0~+3%	0~+3%	0~+3%	0~+3%	0~+3%
Module Efficiency (%)	14.8%	15.1%	15.3%	15.7%	16.0%
Open circuit voltage [V] $V_{oc}$	37.4	37.4	38.1	38.3	38.7
Maximum Power Voltage [V] ( $V_{mpp}$ )	30.2	30.2	30.7	30.9	31.2
Maximum Power Current [A] ( $I_{mpp}$ )	7.94	8.11	8.15	8.25	8.33
Short circuit Current [A] ( $I_{sc}$ )	8.58	8.76	8.80	8.90	9.01

STC: Irradiance : 1000 W/m<sup>2</sup>; Spectrum AM 1,5; Cell temperature: 25°C; Wind 0 m/s



## Mechanical Characteristics

Solar Cell	Monocrystalline silicon 156 x 156 (mm)
No. of Cells	60 (6 x 10)
Dimensions	1640 x 992 x 40 mm (Option 45 / 50 mm)
Weight	19.1 kg
Front Glass	3.2mm (0.13 inches) tempered glass
Frame	Anodized aluminum alloy



## Output

Cable Type	Ø = 4 mm <sup>2</sup>
Lengths	L = 900 mm
Junction Box	PV - JB003 MC4

## Temperature Coefficients

Nominal Operating Cell Temperature (NOCT)	45 ± 2°C
Temperature Coefficient of ( $P_{max}$ )	-0.43% / °C
Temperature Coefficient of ( $V_{oc}$ )	-0.34% / °C
Temperature Coefficient of ( $I_{sc}$ )	0.036% / °C

- Provide the best solutions for photovoltaic power generation and technical support
- Provide Cost-effective products
- Provide 12 Years Quality Warranty
- Power out ≥ 90% in 10 years
- Power out ≥ 80% in 25 years



Simax Green New Energy (Europe) GmbH  
 Mergenthaler Allee 23 / 25  
 65760 Eschborn / Germany  
 Tel.: +49 6196 9739 525  
 Fax: +49 6196 5929 684  
 info@simaxsolar.de  
 www.simaxsolar.de



Simax (Australia) Green New Energy Pty Ltd  
 5 / 78 Frankston Gardens Drive,  
 Carrum Downs, VIC 3210  
 Tel: +61 03 9708 2400  
 Fax: +61 03 9708 2482  
 info@simaxsolar.com  
 www.simaxsolar.com.au



Simax (Suzhou) Green New Energy Co.,Ltd  
 No. 567 Suzhou Road, Taicang city,  
 Jiangsu province, China P.C.: 215400  
 Tel: +86 512 5337 8555  
 Fax: +86 512 5337 8556  
 info@simaxsolar.com  
 www.simaxsolar.com

