



## Innovative

- Consumption analysis for each individual load
- Regional weather forecasts taken into account
- Display of recommended actions for load management

## Simple

- Automatic, intelligent control of loads with maximum 10 SMA radio-controlled sockets
- Convenient commissioning with the plant setup assistant
- Free standard access to Sunny Portal with all basic functions

## Transparent

- Convenient plant monitoring via Sunny Portal
- Overview of all energy flows in the home
- Visualization of the weather forecast and PV yield forecast

## Flexible

- Several standardized meter interfaces
- Individual specifications for controlled devices

## SUNNY HOME MANAGER

The control center for smart energy management

With its standard access to Sunny Portal, the Sunny Home Manager is the ideal solution for simple plant monitoring and intelligent energy management. It provides an overview of all the energy flows taking place in the household, displays recommended actions and is able to control loads via SMA radio-controlled sockets automatically. The device learns the typical consumption pattern of the household and combines this information with a forecast of the plant-specific PV generation. As a result, the Sunny Home Manager enables a much higher self-consumption ratio and a highly efficient use of energy from the environmental point of view.



Precise determination of generation, consumption and self-consumption



Energy data displayed live in Sunny Portal



PV forecast data and variable electricity tariffs taken into account



Info page with recommendations for optimizing load management



Presentation and management of home consumption – even from remote locations



Analysis of power consumed by individual devices via SMA radio-controlled sockets



Safe transmission of energy data



Simple Monitoring via Sunny Portal

Technical data	Sunny Home Manager	
<b>Communication</b>		
Inverter communication	Bluetooth®	
Sunny Portal communication	Ethernet	
<b>Connections</b>		
Inverter	See inverter communication	
Ethernet	10/100 Mbit, RJ45	
Energy meter	3* terminal for connection of S0 cable or D0 reading heads	
<b>Max. number of SMA devices</b>		
Bluetooth	16	
<b>Max. radio range</b>		
Bluetooth in free-field conditions	Up to 100 m (extendable with SMA Bluetooth Repeater)	
<b>Voltage supply</b>		
Voltage supply	External plug-in power supply	
Input voltage	100 V – 240 V AC; 50/60 Hz	
Power consumption	< 6 W (max. 14.3 W)	
<b>Ambient conditions in operation</b>		
Ambient temperature	-25 °C ... +60 °C	
Degree of protection (according to EN IEC 60529)	IP20	
Maximum permissible value for relative humidity (non-condensing)	5 % ... 95 %	
<b>Memory</b>		
Internal	Up to 5 days portal buffer	
Daily energy values	Up to 5 days	
<b>General Data</b>		
Dimensions (W/H/D)	170/124.5/41.5 mm	
Weight	0.22 kg	
Mounting Location	Indoors	
Deployment options	Top-hat rail mounting, wall mounting	
Status display	LEDs	
Language of the manual	German, English, Italian, Spanish, French, Dutch, Portuguese, Greek, Czech	
<b>Features</b>		
Operation	Via Sunny Portal	
Warranty	5 years	
Certificates and approvals	www.SMA-Solar.com	
<b>Accessories</b>		
SMA radio-controlled socket with Bluetooth Wireless Technology	For automatic management of loads	
SMA Bluetooth Repeater	For extension of the maximum Bluetooth radio range	
Type designation	Sunny Home Manager	